

# Five ECU's are Model: 704DPXA60000AA

BRYANT HEATING & COOLING SYSTEMS 7310 West Morris Street, Indianapolis, IN 46231 U.S.A.										MODEL N° DU MODELE 704DPXA60000AA--									
										SERIAL / SERIE 2409C06617									
FACTORY CHARGED WITH R-410A REFRIGERANT																			
PERMISSIBLE VOLTAGE AT UNIT		253	MAX		197	MIN													
VOLTS AC		PH	HZ		RLA		LRA		REF. SYSTEM R-410A		TEST PRESSURE GAGE								
COMPRESSOR		208/230	3	60		16		110		LBS 10		Kg 4.54		HI 450 PSI 3102.3 kPa		LOW 250 PSI 1723.5 kPa			
MOTOR		VOLTS AC	PH	HZ		FLA		HP (W)		MAX. EXTERNAL STATIC PRESSURE		0.5		IN. W.C.					
OUTDOOR FAN		208/230	1	60		1.2		1/5 (149)											
INDOOR FAN		208/230	1	60		7.6		1 (746)		PRESS. STATIQUE EXTÉRIEURE MAX.		125		Pa					
UNIT SUITABLE FOR OUTDOOR USE										CHARGE UNIT PER INSTALLATION INSTRUCTIONS									
ACCESSORY HEATER MODEL NUMBER		CHECK HERE	VOLTS	PH	HZ	ELEC HEAT FLA	MIN. CKT AMPS (MCA)		MAXIMUM OVERCURRENT PROTECTION DEVICE (Per NEC)		MINIMUM UNIT DISCONNECT								
NONE			208/230	3	60	—	28.8		40		29		112						
CPHEATER055A00			208/230	3	60	10.4/12	28.8/28.8		40/40		28/29		112/112						
CPHEATER056A00			208/230	3	60	20.8/24.1	35.5/39.6		40/40		33/36		112/112						
CPHEATER068A00			208/230	3	60	20.8/24.1	35.5/39.6		40/40		33/36		112/112						
CPHEATER057A00			208/230	3	60	31.2/36.1	48.5/54.6		50/60		45/50		112/112						
CPHEATER058A00			208/230	3	60	31.2/36.1	48.5/54.6		50/60		45/50		112/112						
CPHEATER059A01			208/230	3	60	41.4/47.9	61.3/69.4		70/70		56/64		112/112						
-			-	-	-	-	-		-		-		-						