

SPECIAL PACKAGING INSTRUCTION			CODE ID 98747	SPI NO. (TPD) F01-626-1688	
			SHEET 1 OF 4		
PART OR DRAWING NO. 114-05190-2003	NATIONAL STOCK NO. 5995-01-626-1688 AH	CURRENT REV A	ILL. D. NAY P.S. S. PEELER		
ITEM NOMENCLATURE CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL BRANCHED		ORIGINAL DATE 16270	CHK. K. RESTORFF AUTH. N. CORDONADO		
MILITARY PRESERVATION IAW MIL-STD-2073			PACKING AS SPECIFIED BELOW AND BILL OF MATERIALS		
SERVICEABLE METHOD: 41		LEVEL	SPEC	STYLE TYPE	CL VRTY GR TR
UNSERVICEABLE METHOD: 41		A	ASTM D6880	4	2 B
QUP 001		B	ASTM D6880	4	2 A
ICQ 000				LEVEL A	LEVEL B
CLEANING & DRYING: IAW MIL-STD-2073		GROSS CU FT		4.338	4.338
PRESERVATIVE: N/A		GROSS WT LBS		139	139
		DESIGN FRAGILITY G		110	110
MARKING IAW MIL-STD-129			LENGTH WIDTH DEPTH		
SPECIAL MARKINGS:			CNTR I.D.		
A) SPI NO. F01-626-1688			LEVEL A:		
MARK THE SPI NUMBER ON THE IDENTIFICATION SIDE OF CONTAINER.			LEVEL B:		
B) REUSABLE CONTAINER & DUNNAGE DO NOT DESTROY.					
CLOSURE			CNTR O.D.		
LEVEL A: IAW: ASTM D6880			LEVEL A:		
LEVEL B: IAW: ASTM D6880			LEVEL B:		
			ITEM DIM		
			ITEM WT.		
			26 22 6		
			100 LBS		
REVISIONS					
LTR	DESCRIPTION				DATE
A	ADDED DISTRIBUTION STATEMENT AND DESTRUCTION NOTICE, UPDATED BOM				18261
DISTRIBUTION STATEMENT D: DISTRIBUTION AUTHORIZED TO DEPARTMENT OF DEFENSE AND U.S. DOD CONTRACTORS ONLY, ADMINISTRATIVE OR OPERATIONAL USE, 17 SEPTEMBER 2018. OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO 406 SCMS/GULAA, (PACKAGING DIVISION), HILL AFB, UTAH 84056.					
DESTRUCTION NOTICE: FOLLOW THE PROCEDURES IN DOD 5220.22-M, NATIONAL INDUSTRIAL SECURITY PROGRAM OPERATING MANUAL (NISPOM), SECTION 5-705, OR DOD 5200.1-R, INFORMATION SECURITY PROGRAM, CHAPTER VI. FOR UNCLASSIFIED, LIMITED DOCUMENTS, DESTROY BY ANY METHOD THAT WILL PREVENT DISCLOSURE OF CONTENTS OR RECONSTRUCTION OF THE DOCUMENT.					

SPI NO. F01-626-1688

SPECIAL PACKAGING INSTRUCTION	CODE ID 98747	SPI NO. (TPD) F01-626-1688
ITEM NOMENCLATURE CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL BRANCHED		SHEET 3 OF 4
<p>CAUTION NOTICES</p> <p>NOTICE 1: ASSETS PACKAGED IN PREVIOUS EDITIONS OF THIS SPI DO NOT REQUIRE REPACKAGING IF THE INTEGRITY OF THE SPI IS MAINTAINED.</p> <p>NOTICE 2: SEE SPIRES FOR A COMPLETE LISTING OF NSN's ASSIGNED TO THIS SPI.</p> <p>NOTICE 3: PACKAGING MATERIAL MAY BE SUBSTITUTED IF IT MEETS THE REQUIREMENTS OF MIL-STD-2073, PROVIDES EQUAL OR BETTER PROTECTION AND THERE IS NO INCREASED COST TO THE GOVERNMENT.</p> <p>NOTICE 4: OVERSEAS AND FMS PACKAGING MUST MEET THE REQUIREMENTS OF LEVEL A PACKAGING.</p> <p>INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES REVISION OF ISPM NO. 15 REVISION OF WOOD PACKAGING MATERIAL FOR INTERNATIONAL TRADE</p> <p>THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES).</p> <p>WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT:</p> <p>ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKAGING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."</p> <p>NOTES</p> <ol style="list-style-type: none">1. WRAP ENDS OF ITEM USING REF.-8 AND SECURE WITH TAPE, REF.-7.2. WRAP ITEM USING REF.-6 PRIOR TO PLACING IN BAG, REF.-5, THEN EVACUATE AIR AND SEAL BAG.3. USE ADDITIONAL CUSHIONING, REF.-8 TO INSURE A SNUG FIT.		

SPECIAL PACKAGING INSTRUCTION

CODE ID
98747

SPI NO. (TPD)
F01-626-1688

ITEM NOMENCLATURE
CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL BRANCHED

SHEET 4 OF 4

