CONCRETE LOOK

UNITY™

COLORBODY™ PORCELAIN

daltile®

IMAGINE WHAT'S POSSIBLE™

UNITY™

COLORBODY™ PORCELAIN

Chic Blend of Popular Stone Visuals

Your space requires peak performance and outstanding durability. Your design, however, calls for contemporary style and sophistication. This can be achieved with the ColorBody™ porcelain line, Unity™. This double-load porcelain tile is one of the toughest tiles available, yet it doesn't compromise on style. Style and performance unite with Unity from Daltile.

- DOUBLE-LOAD PORCELAIN PRODUCED WITH MICROPOWDERS
  - Offers the high performance of double-load ColorBody™ porcelain
  - Creates a more uniform visual for contemporary minimalist look
- TRU-EDGE™
  - Rectified for a seamless, unified look in large areas
- CONTEMPORARY COLOR PALETTE & VISUAL
  - Available in six contemporary colors
  - Textured, unpolished and polished surfaces provide options for any space

CONCRETE LOOK

USAGE

FLOOR

WALL

COUNTERTOP

SHOWER FLOOR

EXTERIOR FLOOR

SPECIAL FEATURES

STEPWISE™

TRU-EDGE™

MADE IN THE U.S.A.

LARGE FORMAT

MOSAIC/ DECO

ENCAUSTIC

TERRAZZO

PAVER

CUSTOMIZE

FLEXFIT™

PT TECHNICAL PORCELAIN

LOW HIGH

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

Cover photo features Avorio and Tobacco 12 x 24 field tile and Urban Metals™ Gunmetal 2 x 12 spiral border on the floor.
Above photo features Tobacco 24 x 24 field tile on the floor.

UNITY™

COLORBODY™ PORCELAIN

CONCRETE LOOK

SIZES:

- 24 x 24 Floor Tile
- 12 x 24 Floor Tile
- 12 x 12 Floor Tile
- 12 x 12 Modern Linear

FINISHES: MATTE | GLOSSY | TEXTURED

COLOR PALETTE



AVORIO | BEIGE | TAUPE | ASHGREY | GRIGIO | NERO

POLISHED FIELD TILE

AVORIO P400 | BEIGE P401 | TAUPE P407

ASHGREY P405 | GRIGIO P402 | NERO P406

UNPOLISHED FIELD TILE

AVORIO P400 | BEIGE P401 | TAUPE P407

ASHGREY P405 | GRIGIO P402 | NERO P406

SLIP RESISTANT | WATERPROOF | STAINPROOF | DENTPROOF | SCRATCH-RESISTANT* | FIRE-RESISTANT | INDOOR/OUTDOOR | SIMPLICLEAN™

*Applicable to products with Matte and Textured Finishes

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

UNITY™

COLORBODY™ PORCELAIN

TEXTURE FIELD TILE

AVORIO P400

BEIGE P401

TAUPE P407

ASHGREY P405

GRIGIO P402

NERO P406

DECORATIVE ACCENTS



AVORIO P400
12 x 12 Modern Liner



BEIGE P401
12 x 12 Modern Liner

TAUPE P407
12 x 12 Modern Liner



ASHGREY P405
12 x 12 Modern Liner



GRIGIO P402
12 x 12 Modern Liner



NERO P406
12 x 12 Modern Liner

UNITY™

COLORBODY™ PORCELAIN

CONCRETE LOOK

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
24 x 24 Floor Tile+	(23-1/2" x 23-1/2") (59.7 cm x 59.7 cm)	3/8"	15.28	4
12 x 24 Floor Tile	(11-11/16" x 23-1/2") (29.7 cm x 59.7 cm)	3/8"	15.26	8
12 x 12 Floor Tile+	(11-11/16" x 11-11/16") (29.7 cm x 29.7 cm)	3/8"	10.44	11
12 x 12 Modern Liner†	(11-11/16" x 11-11/16") Sheet (29.7 cm x 29.7 cm Sheet)	3/8"	N/A	11

+ Available in Unpolished and Polished only

† Available in a combination of surfaces

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓**
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Unpolished and Textured only

** Textured only

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

TRIM

Type	Number	Size	Pieces/ Carton
Bullnose	S-43C9S	3 x 12	30
Cove Base	S-36C9TA	6 x 12	20
Cove Base Outcorner	SC-36C9TA	1 x 6	10

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Medium (V2)

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

ZEROTOX Healthy Homes | Healthy Planet

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

LEARN MORE

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at **daltile.com.**

daltile® IMAGINE WHAT'S POSSIBLE™

©2021 Daltile (9/21)