

Salient Characteristics

Scissor Lift

- OSHA Recognized NRTL Certification
- **Platform Height (Elevated)** – Indoor-25.5 ft / Outdoor-21 ft
- **Platform Capacity** – Indoor-507-lb / Outdoor-275 lb
- **Capacity on Platform Extension** – Indoor-265 lb / Outdoor-265 lb
- **Number of Occupants** – Indoor-2 / Outdoor-1
- **Lift/Lower Time (No Load)** – Indoor-33/36 seconds / Outdoor-33/36 seconds
- **Lift / Lower Time (Rated Load)** – Indoor-39/29 seconds / Outdoor-39/29 seconds
- **Maximum Drive Height** – Indoor-21 ft / Outdoor-21 ft
- **Weight** – Indoor-4400 lb / Outdoor-4400 lb
- **Max Ground Bearing Pressure** – Indoor-107 psi / Outdoor-107 psi
- **Drive Speed (Lowered)** – Indoor-2.75 mph / Outdoor-2.75 mph
- **Drive Speed (Raised)** – Indoor-.5 mph / .5 mph
- **Gradeability** – Indoor-25% / Outdoor-25%
- **Max Tilt Rating (Side-to-Side)** – Indoor-1.50 Degrees / Outdoor-1.50 Degrees
- **Max Tilt Rating (Fore and Aft)** – Indoor-3.50 Degrees / Outdoor-3.50 Degrees
- **Turning Radius (Inside)** – Indoor-Zero / Outdoor-Zero
- **Turning Radius (Outside)** – Indoor-88.2 in / Outdoor-88.2 in
- 4 x 6v 220 amp-hr Batteries
- 27 amp Charger
- 24v DC Drive
- Tire – 16 x 5 in
- Multi-Disc Friction Brakes
- 3.2 gal hydraulic system capacity
- Fixed Displacement Gear Hydraulic Pump
- Active Pothole Protection System
- All Motion Alarm
- Analyzer Port for Diagnostics
- Battery Condition Indicator
- CAN-Enabled Charger
- Diamond Tread Steel Deck
- Dynamic Braking
- Electric Drive
- Foot-Actuated Deck Extension
- Fork Lift Pockets
- Greaseless Kingpin Joints
- Horn
- Hourmeter
- Lanyard Attach Points
- Lifting and Tie Down Points
- Load Sensing System
- Lubrication Free Scissor Arm Bushings

- Manual Descent Cable
- Movable, Removable Platform Control
- Nickel Plated Pins
- Proportional Controls
- QuikFold Rails
- Removable Ladder
- Scissor Maintenance Prop
- Self-Closing Gate
- Steel Swing-Out Doors
- Tilt Alarm and Light
- Variable Tilt Visual Zone Indicator