

SALIENT CHARACTERISTICS

“BRAND NAME OR EQUAL TO CAB CADET”

CUB CADET PRO Z 972 SDL-EFI

Cub Cadet Pro Z 972 SDL-EFI - 38.5 HP 999cc Kawasaki FX1000; Self-leveling seat; Rear dual wheels; Floating, fabricated 72" triple 7-gauge deck w/power deck lift, maintenance-free spindles, heavy duty 16cc Parker HTG transmissions, Adjustable ROPS.

1. 72" triple-7-gauge fabricated steel cutting deck with top, bottom and side reinforcements
2. Lock-in or out self-leveling air-ride seat with 30 degrees of side-to-side swivel/15 degrees of travel left or right.
3. Dual rear wheels and weighted front rims give this steep slope mower traction on up to a 46% grade. 12-volt outlet kit and electronic power deck lift included
4. 3-year limited commercial warranty (no hour limitations) and 5 years / 1,750-hour limited deck construction warranty

ENGINE

- **Engine Brand** Kawasaki®
- **Engine Model** FX Series EFI
- **Engine Model Number** 1000V
- **Engine Displacement** 999cc
- **Engine Output** 38.5HP
- **Starter Type** Electronic
- **Fuel Tank Capacity** Dual 7.45 gal. US (28.2 L)
- **Cylinders** Twin
- **Engine Start** Ignition Key
- **Engine Oil Capacity** 2.0 qt. US (1.89 L)
- **Lubrication** Fully pressurized
- **Charging System** 15 amp regulated
- **Fuel Gauge** Electronic
- **Choke** Auto-Choke
- **Air Filter** High Density
- **Oil Filter** Yes
- **Fuel Delivery** Electronic Fuel Injection (EFI)

BATTERY

- **Battery** 310CCA AGM battery; Relay/Fuse terminal block; 30 AMP voltage regulator

DRIVE SYSTEM

- **Transmission** Parker® heavy duty HTG 16cc pump / 310cc wheel motor with oversized wheel bearings
- **Forward Speed** 14 mph / 22.5 km/h
- **Reverse Speed** 6 mph / 9.5 km/h

CUTTING DECK

- **Deck Cutting Width** 72 in
- **Deck Material** triple-7-gauge fabricated steel
- **Deck Engagement (PTO)** Electronic with quick reset
- **Deck Construction** Floating, fabricated 7 ga (0.187") steel and adjustable rear striping rollers
- **Spindle Construction** Maintenance-free cast aluminum housing
- **Blade(s)** 3 high-lift Marbain® blades / 18,500 fpm (approx.)
- **Deck Lift** Electro-hydraulic assist quick-lift design
- **Cutting Height Range** 1" to 5" in 1/4" increments
- **Anti-Scalping** 4 front deck gauge wheels
- **Deck Positions** 16

WARRANTY

- **Deck Shell Warranty** 5 year / 1,750-hour limited deck construction warranty
- **Commercial Warranty** 3 year / no hour limit commercial warranty

CHASSIS

- **Frame** Fully welded, 3/8" x 5" laser-cut steel
- **Front Axle** 2" x 3" solid with Isolation dampening system, 1/2" thick steel
- **ROPS** 2" x 2" foldable 3-position with low profile
- **Bumper** 5/16" Thick Steel rear engine guard/pre-drilled mounting points for attachments with integrated rear hitch
- **Rear Tow Hitch** Bolt-On hitch std

CONTROLS

- **Cruise Control NA**
- **Brakes Cruise Control NA**
- **Brakes** Hand-operated lever with integrated hydro pump release lever
- **Steering Control** Quick-adjust steering column w/ power steering
- **Operator Control** Low-profile throttle lever Hand-operated lever with integrated hydro pump release lever
- **Steering Control** Quick-adjust steering column w/ power steering
- **Operator Control** Low-profile throttle lever.

WHEELS

- **Rear Tires** 25"x9"-12" HD Traction Tread
- **Front Tires**16"x6.5"-8"Kenda K505
- **Tire Tread** Heavy-Duty traction tread

DIMENSIONS

- **Dimensions L/W/H** 88" / 74" / 85"
- **Weight (approx.)**1,885 lbs