

## Bid Specifications

### Street Sweeper

Equipment shall be furnished fully assembled, operational, and serviced.

Two sets of Operators, Service, and Parts manuals must be supplied. 2 Each Service Kits B and C

1 Easy Mount wear Kit, 10- 36" Steel Gutter Brooms 1-Weed Cutting Broom, 1 Spare front and rear rim and tire.

Engine: One, Tier IV Diesel Engine 4cyl with at least 135hp and no more than 161hp which powers the sweeper and vacuum unit.

Roof mounted oil cooler

Drivetrain: Hydrostatic continuously variable

Suction: 15,000 cfm

Brooms: 35 inch brooms with speed of 0 to 210rpm to include 3<sup>rd</sup> broom option with joystick control.

Fuel Tank: 28 Gal minimum

Water Tank 160 Gal minimum

Sweeping width of 95in 2 brooms, 134in with articulating 3<sup>rd</sup> broom

Turning radius of 199in or less.

Suction nozzle dimension of 4.7in x 24.8in with a suction tube diameter of 8.9in.

Stainless steel 6.5 cubic yard hopper

On board pressure washer with high pressure pump, hose and gun

Wheelbase not to exceed 71.5 inches

Training for operators must be provided.

Cab will have: 180 degree safety glass

Air ride seat

3 cameras and one screen

Floor window for view of suction nozzle

AM/FM/CD Radio