

OPTION MCTL FY23
Available on GSA Item 89J

1. EXPORT ENGINE MUST BE JP8 COMPATIBLE with 5 Year/ 100,000 OEM Warranty
2. PAINT CAB AND BODY NON-GLOSS PAINT #34094 GREEN
 - a. CUT INTO THE RUBBER ON THE DOOR JAMBS
 - b. ALL EXPOSED PORTIONS ON THE DOORS PAINTED
 - c. PAINT THE UNDER SIDE OF HOOD AND CUT THE FENDERS INTO THE WHEEL WELLS
 - d. PAINT BUMPERS
3. MILITARY MARKINGS shall be stenciled on the Front and Rear Bumper and Below the Front Driver and Passenger Doors. They shall be 3" and will be US NAVY on one line and REG Number on the second line.
4. TIRE PRESSURE shall be stenciled in 1" letters/numbers. Color shall be non-gloss black
5. Wheels to be painted non gloss black, do not paint front hubs
6. Raise rear axle vent to top of frame rail
7. Install canvas Seat Covers or equal on the seats.
8. The following GSA options are required and must be selected by the ordering agency
 - a. 115V
 - b. UTC
 - c. MIL
 - d. YD
 - e. CBU
 - f. MRS
 - g. CTB
 - h. MEW
 - i. RBV
 - j. WR2
 - k. SU4
 - l. RH4V
 - m. WR
 - n. TT
9. One of the upfitter switches shall be used to disconnect the back-up alarm from the reverse circuit when the switch is activated, a second to control MRS
10. RBV to be step bars tubular, powder coated non gloss black
11. Furnish NATO 12 pin electrical connector 12V DC located at rear hitch
12. Furnish Combination Ball Hitch/Pintle Hook 10 Ton Capacity with locking pin
13. MBG to be Warren with headlight protectors or equal.
14. WR2, to be a minimum of 40,000 GCWR
15. Vinyl Flooring
16. Front axle to be 7500 lbs GAWR
17. Following Vehicle information shall be provided
 - a. Primary Model
 - b. Cage Code
 - c. VIN
 - d. Engine S/N
 - e. Engine Model
 - f. Engine MFR
 - g. Transmission S/N
 - h. Transmission Model

OPTION MCTL FY23
Available on GSA Item 89J

18. Chrome Badging will be removed or subdued/painted non gloss black
19. Daytime running lights shall be user programmable
20. Furnish and install a Tuffy Under seat Lockbox SKU 316
21. A preliminary design review shall be conducted
22. A critical design review shall be conducted at the upfitter

Delete standard utility body; add KNAPHEIDE body (per figure 6108DL-44) or equivalent with the following capabilities:

MAINTENANCE BODY

- 44" TALL COMPARTMENTS
- Right Vertical 1 AND Right Vertical 2 COMPARTMENT RAISED TO 60" HEIGHT
- 21.5" REAR WORK BENCH BUMPER WITH THROUGH COMPARTMENT
- RH4V WITH SAFETY CHAIN EYES
- 1/4" SMOOTH STEEL WORK SURFACE
- SLAM ACTION TAILGATE
- MASTER LOCKING SYSTEM
- LIGHT BOXES MOUNTED ON THE REAR OF COMPARTMENTS W/LED LIGHTS
- SLIDE OUT REAR STEP WITH HANDRAIL

COMPARTMENT CONFIGURATION:

- LV1: DRAWER UNIT WITH 5-3", 2-5", 1-7" ROLLOUT DRAWERS
- LH: (1) ADJUSTABLE SHELF
- LRV1:(2) ADJUSTABLE SHELF
- RV1: OXY-ACET BOTTLE HOLDER ASM-(2) BOTTLE HOLDER, COMPARTMENT VENT
- LH: (1) ADJUSTABLE SHELF
- RRV1: AIR HOSE REEL,.50" F/L/R,

MISC:

- AMERICAN EAGLE MODEL 45R HYDRAULIC DRIVEN ROTARY SCREW COMPRESSOR or Equal
- .50"X50' SPRING REWIND HOSE REEL MOUNTED IN REAR CRANE COMPARTMENT
- .50" FILTER/REGULATOR/LUBRICATOR
- 25 TOTAL GALLON AIR TANKS MOUNTED UNDER BODY
- Mounting platform and electrical supply for MILLER-BOBCAT 250
- RH4V to be CLASS V 2" REAR RECEIVER HITCH RATED AT 18,500 LBS. MAX TRAILER WEIGHT
- BODY PRIME PAINT, COMPLETE IMMERSION IN ELECTRODEPOSITION EPOXY PRIMER
- Rear Mud Flaps

OPTION MCTL FY23
Available on GSA Item 89J

- Undercoating
- Diesel Fuel Only Label