

MATERIAL ORDERING DATA

MIL-S-24149

IDN: **N4523A - 2286 - 1006**

ICN: **38CTB469W2** KO: **S09** KOI: **023**


Paragraph 6.2 Ordering Data

- A. **MIL-S-24149C, STUDS, WELDING, AND ARC SHIELDS (FERRULES), GENERAL SPECIFICATION FOR, dated 27 MAR 1989. REINSTATEMENT NOTICE 2, dated 21 AUG 2000 INCLUDING AMENDMENT 1, dated 01 DEC 1989.**
- B. Current issue of DODISS is to be cited in the solicitation (see 2.1.1 and 2.2).
- C. Type of stud and arc shield (see 1.2):
- ☒ Type I – Carbon steel studs, fluxless weld-end
 - ☐ Type II – Carbon steel studs, solid flux or aluminum flux coated weld-end
 - ☐ Type III – Aluminum alloy studs, bulb weld-end
 - ☐ Type IV – Aluminum alloy studs, cone protection weld-end
 - ☐ Type V – Corrosion-resistant steel studs, solid flux weld-end
 - ☐ Type VI – Carbon steel studs, tipped or pointed weld-end
 - ☐ Type VII – Aluminum alloy studs, tipped or pointed weld-end
 - ☐ Type VIII – Corrosion-resistant steel studs, tipped or pointed weld-end
- D. Applicable Military Specification Sheet part numbers: **N/A**
- E. First article inspection is not required. (see 3.2, 4.3 and 6.4)
- F. Type of protective coating or treatment (see 3.6): **N?A**
- G. If inspection conditions are other than specified (see 4.4.2): **N/A**
- H. Level of preservation and packing requirements (see 5.1): **N/A**
- I. When fire-retardant requirements are required (see 5.1(a)(1)(2): **N/A**

Additional Data Requirements:

ASTM-B446, UNS N06625GRADE 1, COND HF ANNEALED AND PICKLED

Prepared By: **Kurt Weber**
Code: **250.2**



STUD, FAIRING SUPPORT MOUNT

MATERIAL: INCONEL 625 PER ASTM-B446, GRADE 1.
MIN YIELD 80 KSI

QUANTITY REQD: 32/AFT ARRAY 

STUD 0.625-11UNC-2A X 2.66 L NICRMDCB ASTM-B446-GR1 COND HF ANL PICKLED